



2100Q Portable Turbidimeter

| | |
|------------|--------------|
| Product #: | 2100Q01 |
| USD Price: | Contact Hach |
| Available | |

Easiest calibration and verification with accurate results every time.

Measuring and monitoring turbidity is crucial for various industrial and municipal applications, and Hach's portable turbidimeter, the 2100Q, provides unsurpassed ease of use and accuracy. With over 80 years of experience, Hach is a leader in turbidity measurement and has consistently developed reliable and durable instruments for customers.

The portable 2100Q turbidity meter is ideal for use in the field or around the plant. It is easy to carry around and take multiple measurements from various collection points in your treatment process. With its intuitive user interface, the 2100Q makes it easy to take measurements and perform calibration and verification. Storing and transferring data from a portable turbidimeter has never been easier.

There is also an optional USB+Power module for the 2100Q portable turbidimeter, which allows you to transfer your data directly to a computer.

The 2100Q portable turbidimeter is compliant with USEPA Method 180.1 design criteria.

Easy on-screen assisted calibration and verification

Save time and get accurate results with an easy-to-follow interface that eliminates the need for complicated manuals to perform routine calibrations. Single-standard RapidCal™ calibration offers a simplified solution for low level measurements, while ensuring you meet reporting requirements.

Simple data transfer

Data transfer with the optional USB+Power Module is simple, flexible, and doesn't require additional software. All data can be transferred to the module in XML format and easily downloaded to your computer with a USB connection, providing superior data integrity and availability.

Accurate for rapidly settling samples

The innovative Rapidly Settling Turbidity™ mode provides accurate measurements for difficult to measure, rapidly settling samples. An exclusive algorithm that calculates turbidity based on a series of automatic readings eliminates redundant measurements and estimating.

Convenient data logging

Up to 500 measurements are automatically stored in the instrument for easy access and backup. Stored information includes: date and time, operator ID, reading mode, sample ID, sample number, units, calibration time, calibration status, error messages, and the result.

Optical system for precision in the field

The two-detector optical system compensates for color in the sample, light fluctuation, and stray light, enabling analysts to achieve laboratory-grade performance on a wide range of samples, even under difficult site conditions.

Specifications

| | |
|----------------------------|-----------------------------------|
| Accuracy: | ± 2 % of reading plus stray light |
| Battery Requirements: | 4, AA |
| Certifications: | CE certified |
| Compliance Certifications: | CE/WEEE |

| | |
|-------------------------------|--|
| Data Logging: | 500 records |
| Dimensions (H x W x D): | 77 mm x 107 mm x 229 mm |
| Display Size: | 240 x 160 pixels |
| Display Type: | Graphic LCD |
| Enclosure Rating: | IP67 |
| Height : | 3.0 in |
| Includes: | Instrument, case assembly, 4 AA alkaline batteries, 6 sample cells, StablCal ampule kit, silicone oil, oiling cloth, manual. |
| Interface: | Optional USB |
| Light Source: | tungsten filament lamp |
| Manual Languages: | English, French, German, Italian, Spanish, Portuguese (BR), Portuguese (PT), Bulgarian, Chinese, Czech, Danish, Dutch, Finnish, Greek, Hungarian, Japanese, Korean, Polish, Romanian, Russian, Slovenian, Swedish, Turkish |
| Max. operating humidity: | 90 % |
| Measurement Method: | Ratio turbidimetric determination using a primary nephelometric light scatter signal (90°) and transmitted light scatter signal |
| Measurement Modes: | Normal (Push to Read), Signal Averaging, Rapidly Settling Turbidity |
| Operating Temperature Range: | 0 - 50 °C |
| Power Requirements: | 100 - 240 V AC / 50/60 Hz (with optional Power or USB+Power module) |
| Power Requirements (Hz): | 50/60 Hz |
| Power Requirements (Voltage): | 100 - 240 VAC |
| Power Supply: | Batteries (see Battery Requirements) or Optional Power Supply |
| Range: | 0 - 1000 |
| Range 2: | NTU |
| Reading Modes: | Normal (Push to Read) Signal Averaging Rapidly Setting Turbidity |
| Regulatory: | EPA Method 180.1 |
| Repeatability: | ± 1 % of reading or 0.01 NTU , whichever is greater |
| Response Time: | 6 s in normal reading mode |
| Sample Cell Compatibility: | 25 mm x 60 mm round |
| Sample Requirements: | 15 mL (0.5 oz) |
| Sample Volume: | 15 mL |
| Signal Averaging: | Selectable on/off |
| Storage Conditions: | -40 °C to 60 °C |
| Stray Light: | < 0.02 NTU |
| Units: | NTU |
| User Interface: | Button Graphic User Interface |
| User Interface Languages: | English, French, German, Italian, Spanish, Portuguese (BR), Portuguese (PT), Bulgarian, Chinese, Czech, Danish, Dutch, Finnish, Greek, Hungarian, Japanese, Korean, Polish, Romanian, Russian, Slovenian, Swedish, Turkish |
| Warranty: | 1 year |
| Weight: | 0.53 kg without batteries |

What's in the box?

Portable turbidimeters are supplied with four AA alkaline batteries, a carrying case with insert, primary calibration standards in 1" sealed vials (20, 100, 800 NTU), 10 NTU primary verification standard, 6 sample cells with screw-tops, instrument manual (printed and CD-ROM), quick start guide, silicone oil and oiling cloth.